

LISTING OF THE CLAIMS

19. (Previously Presented) A computer-implemented method for a mobile network, comprising:
displaying a link to a resource with a mobile terminal;
automatically determining the location of the mobile terminal;
if the link is selected, automatically employing the location of the mobile terminal to
determine content that is related to the linked resource and also related to the location of the mobile
terminal; and
enabling the mobile terminal to display the related content.
20. (Previously Presented) The computer-implemented method of Claim 19, wherein
automatically determining the location of the mobile terminal comprises automatically determining
the location of the mobile terminal at periodic intervals.
21. (Previously Presented) The computer-implemented method of Claim 19, wherein
automatically determining the location of the mobile terminal comprises automatically determining
the location of the mobile terminal if the link is selected.
22. (Previously Presented) The computer-implemented method of Claim 19, wherein
automatically employing the location includes:
communicating the location of the mobile terminal to an application server; and
searching a database in the application server for reseller information that is associated with
the linked resource and the location of the mobile terminal, wherein the reseller information is the
related content.
23. (Previously Presented) The computer-implemented method of Claim 19, wherein
automatically determining the location includes:
determining a network address of the mobile terminal; and
mapping the network address to a mobile identifier integrated services digital network
number; and

28. (Previously Presented) A mobile terminal that is configured for operation in a mobile network, comprising:

- a transceiver that configured to communicate over a network;
- a memory including logical instructions stored therein; and
- a processor that is configured to enable actions based on executing the logical instructions,

wherein the actions include:

- displaying a link to a resource,
- storing a location of the mobile terminal in the memory, wherein the location of the mobile terminal is determined automatically, and
- if the link is selected:
 - communicating the selected link and the location of the mobile terminal to the application server.

29. (Previously Presented) The mobile terminal of Claim 28, wherein the actions further include:

- receiving content related to the linked resource and the location of the mobile terminal from the application server, and
- displaying the related content with the mobile server.

30. (Previously Presented) The mobile terminal of Claim 28, wherein the location of the mobile terminal is automatically determined by:

- communicating radio signals;
- measuring the radio signals;
- receiving the measurements of the radio signals; and
- storing the measurements.

31. (Previously Presented) The mobile terminal of Claim 30, wherein:

the transceiver is further configured to receive the measurements of the radio signals, and wherein the actions further include calculating the location of the mobile terminal based on the measurements.

32. (Previously Presented) The mobile terminal of Claim 30, wherein the actions further comprise:

- measuring the radio signals generated by the mobile terminal during idle periods;
- storing the measurements;
- determining an arrival time of a first detectable path; and
- determining when the idle periods occur.

33. (Previously Presented) The mobile terminal of Claim 30, wherein the actions further comprise:

- receiving interactive betting content that enables a bet to be made from the mobile terminal; and
- if the bet is made, automatically receiving the link such that the link is related to the bet.

34. (Previously Presented) An application server for a mobile network, comprising:

- a transceiver that is configured to communicate over a network;
- a memory that includes a database and logical instructions, and
- a processor that is configured to enable actions based on executing the logical instructions, wherein the actions include:
 - providing a link to a resource to a mobile terminal;
 - receiving an automatically determined location of the mobile terminal if the link is selected,
 - searching the database to determine content that is related to the link and the automatically determined location, and
 - providing the related content to the mobile terminal.

35. (Previously Presented) A carrier wave signal for a mobile network, wherein the carrier wave signal enables actions, including:

- providing a link to content to a mobile terminal;
- employing the location of the mobile terminal to determine content that is related to the linked resource and also related to the location of the mobile terminal, wherein the location of the mobile terminal is automatically determined, and
- providing the related content to the mobile terminal.

36. (Previously Presented) A system for a mobile network, comprising:

- an application server;
- a base station subsystem;
- a location management unit; and
- a mobile terminal that is configured to perform actions, wherein the actions include:
 - displaying a link to a resource,
 - storing a location of the mobile terminal in the memory, wherein the location of the mobile terminal is determined automatically, and
 - if the link is selected:
 - communicating the selected link and the location of the mobile terminal to the application server.

37. (Previously Presented) The system of Claim 36, wherein

- the application server has a database;
- the application server is configured to perform actions, wherein the actions include:
 - searching the database for reseller information that is a matched to the location of the mobile terminal and the selected advertisement image, and
 - providing the reseller information to the mobile terminal if the match is found; and
- wherein

